



Extra Strong Industrial Fan with Guard

Installation

- 1) Read these instructions before installation. A qualified electrician should assemble and install your fan.
- 2) Fan should be mounted at least 2.3M above the floor.
- 3) The “yellow/green” double color cord is the grounding cord.
- 4) A wood frame is recommended to install the fan onto a wall.



Notes

- 1) Be careful not to change the blade angles when installing or cleaning.
- 2) Oil should be dropped in the holes of the motor front and rear end shield periodically.
- 3) Cutting off the power first and using a non-corrosive cleaning agent is recommended when cleaning the fan.
- 4) Damaged power cords should be replaced immediately by qualified electrician.

Mode No.	Size (mm)	Voltage (V)	Frequency (Hz)	Power (W)	Air Delivery (m³/min)	Speed (r/min)	Dimensions (mm)			
							A	B	C	D
FAC3-30	300	230	50	150	30	1400	308	300	96	255
FTAC3-30		380-420								
FAC3-35	350	230	50	200	50	1400	342	350	96	255
FTAC3-35		380-420								
FAC3-38	380	230	50	350	75	1400	380	400	96	263
FTAC3-38		380-420								
FAC3-40	400	230	50	350	75	1400	380	400	96	263
FTAC3-40		380-420								
FAC3-45	450	230	50	550	105	1400	432	450	108	290
FTAC3-45		380-420								
FAC3-50	500	230	50	750	135	1400	478	500	108	321
FTAC3-50		380-420								
FAC3-60	600	230	50	1100	195	1400	572	600	108	331
FTAC3-60		380-420	50							

Connection

